



**SeaJay Marine Group** (313) 402-3685  
www.seajaymarinegroup.com

## **CARING FOR & MAINTAINING YOUR FLEXITEEK DECK**

Your Flexiteek deck requires some care but never needs oiling or special sealants. Prompt attention to spills will keep your deck clean and worry free. Flexiteek is stain resistant; most spills will brush away with soap & water. Should a chemical stain be left to dry out and soap was not enough to remove it, then remove the stain using a piece of 60-grit sandpaper lightly sanding in the same direction as the caulk line pattern. Your deck panels are not a laminate so you may sand them as often as you wish, you will not harm the surface. No sealant is ever necessary after sanding. Sanded areas will appear somewhat lighter after sanding - they will blend in with the surrounding areas within a day or two.

Unlike wood decks Flexiteek can be pressure cleaned if necessary. Wear boat shoes on board or no shoes at all. If black sole shoes are permitted on deck they may scuff the deck area as they do with all decking materials. Treat your Flexiteek deck with the care you would give any teak deck, except the constant oiling and maintenance of teak.

Acetone must never be used to clean the material surface.

Washing Instructions: Use a bristled brush and any boat deck cleaner, rinse with a hose and leave it to air dry.

DO NOT oil, bleach, varnish, paint or lacquer your Flexiteek deck as this will reduce the non-slip characteristic of the material. DO NOT place hot metals on your Flexiteek deck. DO NOT sand with power sanders, they will distort the teak wood appearance

If you wash your walls with bleach, then first spray the Flexiteek deck with water in order to dilute bleach that will run on the deck surface. After walls are washed re-spray both the wall and Flexiteek in order to rinse away any bleach that has pooled on top of your Flexiteek deck.

A patch can repair any portion of the deck that becomes damaged. Contact SeaJay Marine Group for assistance. If you have remaining questions regarding the care and maintenance of your Flexiteek Decking System, please call Flexiteek directly at (954) 973-4335.

Flexiteek is backed with a 5-Year material warranty.

**FLEXITEEK**